Fig 1 Prior art



Fig 2


39(k)
Analogue signal manifold
51
LCD
DAC
41(m)
30
RX
37(i)
AADC
43(n)
TX
CCU
45(o)
33
35(i)
DSP
47(p)
53
Task Memory
DATA Memory
Memory Controller
57
49
Monitor
31
55


61
SM definition
Task definition
Default structures
69
71
73
"ROM"
"RAM"
63
65
67
59
Resource allocation table
Data block list
Data blocks

Fig 3

Fig 4


Triggers
75
CONCENTRATOR
Trigger definition
Selected triggers
77
EXECUTOR
Command blocks to resources
Task block request to memory
Status from resources
Task blocks from memory
31
task ID + SM seq. Nr.
FIFO
81
Status = trigger word + SM seq. Nr.
79
SEQUENCER
SM block request to memory
SM block from memory

Fig 5


SM(Q)
SM(4)
SM(3)
SM (2)
SM (1)
C
C TM N
85
SM table
79
Current state
Trigger word
Free/occupied
Origin. SM seq. Nr.
SCANNER/CONTROLLER
83
Task definition = task ID + SM seq. Nr.
Status = trigger word + SM seq. Nr.
SM block request to memory
SM block from memory

Fig 6


T(Q)
T(5)
T(4)
T(3)
T(2)
T(1)
SM
T
S
S
S
S
Runtime
Task
definition
89
77
SM seq. Number
Task status
Task queues
91
SCANNER/CONTROLLER
87
Status = status word + SM seq. Nr.
Task definition = task ID + SM seq. Nr.
Task block request to memory
Task block from memory
Command block to resource
Status report from resource
Trigger definition to concentrator
Selected Triggers from concentrator

Fig 7



Fig 8



TASK-TRIGGERWORD:

1A,0,0,1,ADC.1.done,DAC.1.done,DSP.1.ready,DSP.2.ready,CU.1.ready,
DSP.1.status,DSP.2.status

Fig 9


DACM
DAC6
DAC5
DAC4
DAC3
DAC2
DAC1
CP
39(k)
41(m)
TX1
TX2
TX3
TX4
TX5
TXI
35(i)
RXJ
RX6
RX5
RX4
RX3
RX2
RX1
37(j)
43(n)
ADC1
ADC2
ADC3
ADC4
ADC5
ADCN
One to One
Subtract
Add
Multiply


CP
39(k)
DAC6
DAC5
DAC4
DAC3
DAC2
DAC1
41(m)
37(j)
RXJ
RX6
RX5
RX4
RX3
RX2
RX1
CP
CP
CP
CP
43(n)
ADC1
ADC2
ADC3
ADC4
ADC5
ADCN
TX1
TX2
TX3
TX4
TX5
TXI
35(i)

Fig 10

Fig 11


51
ASIC1
ASIC2
ASIC
A
B
BUS
Bus controller
FIFO
93(1)
93(2)
93(R)
Resource
DATA PACKAGE
Destination header
Start address
Length
Data block

Fig 12


ASICr-1
A
B
64
ASICr
A
B
Bus controller
FIFO
Bus controller
FIFO
93(r-1)
93(r)
4
1
2
3
4
1
drive
Latch

Fig 13


51
EXTENDED BUS
B
ASICr+1
A
Bus controller
93(r+1)
95
XX = fiber
XY = fiber TX/RX
B
ASICr
A
Bus controller
93(r)
51
BUS

Fig 14


51
Resource bus
Selectable crosspoints resource to A side
95
95
95
95
BUS B-SIDE
64 bits multiplexed
BUS A-SIDE
64 bits multiplexed
Selectable crosspoints cross linking A and B or isolation of section
Selectable crosspoints resource to B side

Fig 15


Resource as source to A
B
LB
R
A
DA
Resource as destination to A
B
DB
A
LA
R
Direction BA
B
LB
A
DA
R
Default
B
DB
A
LA
R
Direction AB
B
DB
A
LA
R

Fig 16a



Fig 16b



Fig 16c



Fig 17


AS/C 11
AS/C 10
R
AS/C 9
Setting/ free -N- -S- -D- -P-
R
Ready/ to use, bus free again
AS/C 8
Request -N- -S- -D- -P-
AS/C 1